




high-bay LED luminaires



The **Galileo Indoor** high-bay luminaires are characterized by a long service life, efficient performance and low maintenance costs, which makes them ideal for illuminating of automated warehouses, assembly halls, extreme high-temperature manufacturing areas, commercial buildings and sports facilities.



Dimensions









Peripheral heat sink in die cast aluminium, powder painted. AEC Thermo Flow technology for optical unit lifetime >100.000hr.

Control gear box in die cast aluminium, powder painted.

Frame and cover of the optical system in die cast aluminium powder painted.


Mounting stand in galvanized and painted steel.

Polyurethane gasket, with no discontinuous points. IP66 Protection degree.


AEC High Performance Optic. Aluminium reflector Class A+. Photobiological Safety Class EXEMPT GROUP.

Flat tempered glass, 4mm thickness. Impact protection IK08. Luminous Intensity Distribution Symmetric optic for indoor lighting, Syr


wide emission



Symmetric optic for indoor lighting, medium emission



Symmetric optic for indoor lighting, elliptic emission



Don't hesitate to contact our experts: Mónika Hosó (T: (06 1) 450 2701); István Hajdrik (T: (06 1) 450 2712); Balázs Lévai (T: (06 1) 450 2711); György Jánoska (T: 06 1) 450-2714)