



surface or low suspended exposed T-ceilings mounted or suspended private label luminaires for traditional T5 fluorescent lamps or LED panels



When high quality should be combined with economics

The double parabolic mirror optics systems of the luminaires can provide glare-free and high efficient illumination for rooms equipped with VDT screens, offices, classrooms, auditoriums, conference and meeting rooms.

Although in case of versions equipped with traditional fluorescent lamps or (even dimmable) electronic gears also excellent, smooth, efficient lighting can be achieved, the LED versions equipped with high quality Tridonic LED panels feature the well-known advantages of solid-state lighting, too:

- **higher luminous efficacy = lower consumption**
- **very long life**
- **UV and IR free light**
- **low maintenance costs**

The LED panels is covered by a diffuse covering, which can provide not only glare free illumination but also protection. On special request, also types equipped with emergency lighting modules or even dimmable versions can be supplied.

Type	Light Source	Energy Efficiency Class, EEC	Cap	Dimensions (mm)	Mass (kg)	Product Code
E-DELUX T5 414M	4 x 14W fluorescent lamps	A	G5	595 x 595 x 55	5.3	1-25-15-0179
E-DELUX T5 424M	4 x 24W fluorescent lamps	A	G5	595 x 595 x 55	5.3	1-25-15-0187
E-DELUX T5 228M	2 x 28W fluorescent lamps	A	G5	195 x 295 x 55	5.0	1-25-15-0177
E-DELUX T5 235M	2 x 35W fluorescent lamps	A	G5	1,495 x 295 x 55	5.6	1-25-15-0178
E-DELUX T5 249M	2 x 49W fluorescent lamps	A	G5	1,495 x 295 x 55	5.6	1-25-15-0186
E-DELUX T5 254M	2 x 54W fluorescent lamps	A	G5	1,195 x 295 x 55	5.0	1-25-15-0185
E-DELUX-LED	4 x 1130lm/48W LED panels	A++	-	595 x 595 x 55	5.3	1-25-19-0120
E-DELUX-LED	2 x 2260lm/48W LED panels	A++	-	1,195 x 295 x 55	5.0	1-25-19-0121
E-DELUX-LED	2 x 2820lm/59W LED panels	A++	-	1,495 x 295 x 55	5.6	1-25-19-0122

Don't hesitate to contact our experts: Mónika Hosó (T: (06 1) 450 2701); István Hajdrik (T: (06 1) 450 2712); Balázs Lévai (T: (06 1) 450 2711); Miklós Bükkös (T: (06 1) 450 2714)